



# PRINTER RUSH

(PTO ASSISTANCE)

27

Application : 10/607,993

Examiner : Williams

GAU : 2879

From: MAS

Location: IDC FMF FDC

Date: 7/7/05

Tracking #: 06110540

Week Date: 6/30/05

DOC CODE	DOC DATE	MISCELLANEOUS
<input type="checkbox"/> 1449	_____	<input type="checkbox"/> Continuing Data
<input type="checkbox"/> IDS	_____	<input type="checkbox"/> Foreign Priority
<input type="checkbox"/> CLM	_____	<input type="checkbox"/> Document Legibility
<input type="checkbox"/> IIFW	_____	<input type="checkbox"/> Fees
<input type="checkbox"/> SRFW	_____	<input type="checkbox"/> Other
<input type="checkbox"/> DRW	_____	
<input type="checkbox"/> OATH	_____	
<input type="checkbox"/> 312	_____	
<input checked="" type="checkbox"/> SPEC	<u>6/30/05</u>	

[RUSH] MESSAGE: Specification dated 6/30/03 page 5  
line 20 text is unclear. please resolve

Thanks

[XRUSH] RESPONSE: \_\_\_\_\_

[Signature]

INITIALS: [Signature]

NOTE: This form will be included as part of the official USPTO record, with the Response document coded as XRUSH.

REV 10/04

7/12  
ABBY

obtaining continued spectrum in discharging.

The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the  
5 accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further  
10 understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

Figure 1 is a longitudinal cross-sectional view showing an entire structure  
15 of a conventional electrodeless lamp system; and

Figure 2 is a graph showing luminosity factor of an electrodeless lamp bulb according to the present invention as comparing to that of the conventional art.

*TJC*  
*7/1/72* 20 *reference*  
ence will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

Figure 1 is a longitudinal cross-sectional view showing an entire structure of a conventional electrodeless lamp system, and Figure 2 is a graph showing luminosity factor by a bulb of an electrodeless lamp system according to the  
25 present invention as comparing to that of the conventional art.